
Encore® Wall Mount Service Sink Faucet

K77-8x06-BR Series

K77-8006-BR K77-8106-BR Compression Valves
Ceramic Valves





Dimensions shown in inches (mm) are for reference only and are subject to change.

1-1/8" (29mm) holes for backsplash are recommended to accommodate 1/2" supply nipples.

1/2" NPT Female Inlets

Operating Temperature: 40-180°F (5-83°C)

Operating Pressure: 15-125psi

Solid heavy duty cast body is specification and commercial quality

Commercial Quality Features

- · Rough chrome finish
- 6" vacuum breaker spout design
- · ADA-compliant lever handles
- · Garden hose thread and pail hook
- · Top support wall bracket
- · Vacuum breaker spout

SPECIFICATIONS:

Wall Mount Service Sink Faucet to be Encore K77-8x06-BR Series in the following configuration:

____ K77-8006-BR Compression Valves Ceramic Valves

Faucet body to be constructed of rough chrome plated brass with lever handles. Supply inlets to be 8" (203mm) on center. Valves to be 1/4-turn with integral check valve to prevent cross-flow and back-flow. Color coded temperature indexes shall meet international standards. 6" vacuum breaker spout to have 3/4" garden hose thread and be equipped with integral pail hook. Top support wall bracket included as standard.